SPERADO

FEATURES

- 1/3” Progressive Scan CMOS
- Max 2.0M (1920x 1080), Full HD(1080p) Resolution
- Enhanced Wide Dynamic Range
- Minimum Illumination: 0 Lux
- Max IR Distance 40 Meter
- 3 Mega Pixel Vari-Focal lens 2.8 - 12 mm
- 3D Digital Noise Reduction
- Weather Proof IP66 Standard
- DSS, Defog, D-Zoom, Privacy Zone, ICR

2 MP VARI-FOCAL BULLET CAMERA
SNI-4320

1080P Full HD | IP66 | PoE | ONVIF

TECHNICAL INFORMATION	
Model	SNI-4320
Image Sensor	1/3” Progressive Scan CMOS
Effective Pixels	1920x 1080
Minimum Illumination	0 Lux (Infrared LEDS Turn On)
WDR	True WDR
Electronic Shutter	Auto / Manual
Lens	3 Mega Pixel Auto Iris 2.8 - 12mm
IR Distance	40 Meter
Stream	Triple • (Main/Sub/Mobile)
Audio	Optional
POE	Optional
Protection	IP-66 Protection Against Rain & Wind
Privacy Zone	16 Zone
HLC(High Light Compensation)	YES
Defog	YES
ONVIF	YES
Digital Noise Reduction	YES
Digital Zoom	YES (8X)
White Balance	ATW etc.
Operation Temperature	-20℃ to 50℃ within 85% RH
Power Supply	DC12V

cmos — 1/3” Progressive Scan CMOS

WDR — TRUE WIDE DYNAMIC RANGE

2.0 MP — 2.0 Mega pixel

0 LUX — MINIMUM ILLUMINATION: 0 Lux

2.8-12MM Vari-focal — 3 MP VARI-FOCAL LENS 2.8-12MM

DAY & NIGHT — TRUE DAY/NIGHT WITH ICR

IR LED — IR DISTANCE 40 METER

DNR — 3D DIGITAL NOISE REDUCTION

12V DC — 12VDC POWER